ACRYLOC INTERIOR PRIMER

PRODUCTS EXP101 Interior Primer

CODES 28400 **PACKAGING** Heavy Duty Plastic Pail

DESCRIPTION Acryloc Interior Primer is an interior, low odour primer-sealer, specifically formulated to offer a quick drying, easy to sand finish. Its superior adhesion makes it compatible with most topcoats. Formulated using water based acrylic binder, titanium dioxide pigment, quality mineral extenders and a powerful fungicide suitable for use in wet areas.

USES Acryloc Interior Primer is excellent for use over painted, unpainted, porous and sealed surfaces to extend the coverage of topcoats. Formulated for easy flow, it sands quickly and easily, leaving a smooth surface for a uniform finish. Recommended for both new and remodelled areas and is great for interior walls, ceilings, doors, trims, panelling etc. The product can be tinted to pastel colours.

SUBSTRATES

- Plasterboard Ceilings and Walls
- Hard Plaster Ceilings and Walls
- Doors, Trims and Panelling
- General Interior Masonry Walls
- Interior Cement Render
- Interior Fibre Cement Sheeting

TECHNICAL SPECIFICATION

- Appearance - Coloured Liquid
- Odour - Low
- Resin Type - Styrene Acrylic
- Application - Brush, Roller, Spray
- S G - 1.3 Kg/Litre
- Coverage - 10-15m²/ Litre
- Volume Solids - 30%
- Weight Solids - 44%
- Dry Time - 1 to 2 Hours

FEATURES & BENEFITS

- Fast Drying
- Excellent Durability
- Low Odour
- Sands Easily
- Easy And Safe Clean Up
- Easy to Apply
- Strong Adhesion
- Tint to Pastel Colours

PERFORMANCE TABLE



acryloc®
building products

February 2009