

# ACRYLOC EXTERIOR PRIMER

**PRODUCTS** EXP102 Exterior Primer

**CODES** 28505

**PACKAGING** Heavy Duty Plastic Pail

**DESCRIPTION** Acryloc Exterior Primer is a low odour, exterior primer-sealer specifically formulated to offer a quick drying, easy to sand finish. Its superior adhesion makes it compatible with most topcoats. Formulated using water based acrylic binder, high-hiding power titanium dioxide pigments, quality mineral extenders and a powerful fungicide suitable for use in humid areas.

**USES** Acryloc *Exterior Primer* is excellent for use over painted, unpainted, porous and sealed surfaces to extend the coverage of topcoats. Formulated for easy flow it leaves a smooth, uniform finish. Recommended for Exterior Masonry Walls, cement render, masonry, and concrete walls. Can be used on most exterior surfaces where a quality primer is required. The product can be tinted to pastel colours.

## SUBSTRATES

- Tilt Panel Walls
- General Exterior Masonry Walls
- AAC (Autoclaved Aerated Concrete)
- Cement Render
- Fibre Cement Sheeting
- Off Form Concrete

## TECHNICAL SPECIFICATION

- Appearance - Coloured Liquid
- Odour - Low
- Resin Type - Styrene Acrylic
- Application - Brush, Roller, Spray
- S G - 1.3 Kg/Litre
- Coverage - 10-15m<sup>2</sup>/ Litre
- Volume Solids - 30%
- Weight Solids - 44%
- Dry Time - 1 to 2 Hours

## FEATURES & BENEFITS

- Fast Drying
- Excellent Durability
- Low Odour
- Sands Easily
- Easy And Safe Clean Up
- Easy to Apply
- Strong Adhesion
- Tint to Pastel Colours

## PERFORMANCE TABLE

