

### ACRYLOC® TIMBER PRIMER

---

**PRODUCT TYPE**

Paints &amp; Coatings

**PACKAGING**

4L Steel Pail

**NOMINAL WEIGHT**6.5 kg

---

**DESCRIPTION**

Acryloc® *Timber Primer* is a superior quality, oil based primer for use on interior & exterior timber throughout the home, office or workspace.

Acryloc Timber Primer is suitable for most wood types and for old and new timber.

---

**FEATURES & BENEFITS**

- Excellent Adhesion
  - Easy to apply
  - No Lead
  - No Mercury
- 

**SUBSTRATE PREPARATION - paint will not adhere to a surface that is dirty.**

- Areas not to be coated should be masked and protected

New Unpainted Surfaces

Fill nail holes, cracks and imperfections with an appropriate patching material and sand smooth.

Remove dust and make sure that the surface is clean, sound and free from contaminants such as oil, mould release, silicone, grease and efflorescence.

Previously painted surfaces

Wash down with sugar soap and rinse with clean water.

Check for soundness of the original coating, remove any loose or flaking paint, fill holes and cracks and sand to an even finish.

Gloss or Semi-Gloss finishes must be completely dulled by sanding.

---

**APPLICATION**

- Mix thoroughly with a broad, flat stirrer, using an upward lifting action before commencing work.
- Thinning is not usually required though thinning with turps may assist when spraying.

**Method**

- Apply one full even coat of Acryloc *Timber Primer* by brush, spray or roller.
- Brushing is recommended on rough surfaces.
- For rolling, a fine nap (6mm) or sponge roller is recommended. Use a 9-11 thou spray tip with Airless spray.

**Important Notes**

- Care should be taken to keep Acryloc *Timber Primer* off windows and adjacent surfaces that are not to be coated.
- Application should be carried out on a day with temperatures above 10°C and below 32°C.
- Clean up with Turps

**OTHER CONSIDERATIONS****Shelf-Life – Unopened Containers**

Maximum two (2) years from date of manufacture when stored correctly

**Transport & Storage**

Pails should not be stacked more than three (3) high during transportation and must be transported upright

Store in a cool place, upright, out of direct sunlight and above 4°C

For further information refer to **MSDS** for *Acryloc Timber Primer*

**TECHNICAL DATA**

APPLICATION METHODS	Roller, Brush, Spray		
SPECIFIC GRAVITY (NOMINAL)	1.55		
THEORETICAL COVERAGE	6-12 m <sup>2</sup> /L per coat, depending on surface		
WET FILM THICKNESS (RECOMM)	80-160 microns per coat sprayed or 1 good roller / brush coat		
DRY TIME (25°C & 50% RH) (APPROX)	Tack Free	Recoat/ Overcoat	Fully Dried
	N/A	24 hours	24 hours
NO. OF COATS	1 coat is recommended		
GLOSS LEVEL	Flat		
SOLVENT FOR CLEANING	Turps		
FLAMMABILITY	Flammable		

**SAFETY & HANDLING**

Refer to **MSDS *Acryloc Timber Primer*** before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on **1300 661 745** or visit **www.acryloc.com.au**

When working with ***Acryloc Timber Primer*** observe the usual precautions for handling turps based products including:

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact
- Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water

Full pails are HEAVY. Wear protective footwear and seek assistance if necessary.

**FIRST AID MEASURES**

**Ingestion** If swallowed, wash out mouth with water. Do NOT induce vomiting. Drink at least two (2) glasses of water. Seek medical attention.

**Eye** Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

**Advice to Doctor** Treat symptomatically

**DISTRIBUTED BY:**

Bizfine Pty Ltd

T/A Acryloc Building Products

174 Cavan Rd

DRY CREEK

South Australia 5094

P: +61 8 8368 0222

F: +61 8 8349 4260

E: sales@acryloc.com.au

W: www.acryloc.com.au