

ACRYLOC® ROOF CLEAN

PRODUCT TYPE

Preparation Products

PACKAGING

20L Heavy Duty Plastic Pail

NOMINAL WEIGHT

21kg

DESCRIPTION

Acryloc *Roof Clean* is a high grade detergent based product designed specifically for releasing moss, lichen, and minor deposits of grease and oil from various substrates to make subsequent pressure cleaning faster and more effective.

Acryloc *Roof Clean* is recommended for cleaning roof tiles as part of a roof restoration and can be used on cement, fibro cement & terracotta roofing tiles, walls, floors, driveways, paths and ceramic tiles where fungal growth, oil or grease has to be removed. Acryloc *Roof Clean* is supplied in Ready to Use form.

SUITABLE SUBSTRATES

- Roofing tiles
 - Driveways & paths
 - Ceramic tiles
 - Cement Render
 - Concrete bricks & blocks
 - Clay brick
-

APPLICATION

When applying Acryloc *Roof Clean* to a roof, it is recommended that Rainwater tanks be disconnected from the guttering system before commencing work. The guttering should remain disconnected until after application of all subsequent coatings and until all residues are washed from the guttering.

Method

- Mix thoroughly with a broad, flat stirrer, using an upward lifting action, or power mixer
- Acryloc *Roof Clean* can be applied using a roller, brush, pad, HVLP spray equipment or airless spray equipment. If applying on roofs, application with a garden type weed sprayer is recommended
- If using airless spray equipment, a 15 thou tip and white gun filter is recommended
- **Indoors and Shaded Areas**
 - Apply Acryloc *Roof Clean* liberally to the surface, agitate with a broom or similar and allow to soak for 1-2 hours. Remove by high pressure cleaning followed by hosing with clean water.
- **Roof Areas**
 - Apply Acryloc *Roof Clean* liberally, leave for 1-2 hours, then pressure clean
 - For heavy moss growth, apply Acryloc *Roof Clean* late afternoon or evening and allow to 'soak' overnight before pressure cleaning
- Acryloc *Roof Clean* must be completely removed, preferably by pressure cleaning.

Important Notes

- Avoid application in full sun, on hot surfaces or in hot windy conditions
- Avoid allowing the material to dry out during the soaking period

Clean-Up

Clean up with water

OTHER CONSIDERATIONS

Shelf-Life – Unopened Containers

Maximum two (2) years from date of manufacture when stored correctly

Transport & Storage

Drums should not be stacked during transportation and must be transported upright

Store in a cool place, upright, out of direct sunlight and above 4°C

For further information refer to **MSDS** for Acryloc *Roof Clean*

TECHNICAL DATA

APPEARANCE	Watery yellow liquid
ODOUR	Low
APPLICATION METHODS	Roller, brush, spray
SPECIFIC GRAVITY (NOMINAL)	~1.04
VOLUME SOLIDS (APPROX)	n/a
WEIGHT SOLIDS (APPROX)	n/a
THEORETICAL COVERAGE	10-15m ² /L per coat at normal dilution
NO. OF COATS	As required, typically 1 coat
SOLVENT FOR CLEANING	Water
FLAMMABILITY	Non-flammable

SAFETY & HANDLING

Refer to **MSDS** for **Acryloc Roof Clean** before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on **1300 661 745** or visit **www.acryloc.com.au**

When working with **Acryloc Roof Clean** observe the following precautions as a minimum:

- Avoid prolonged skin contact and particularly eye contact
- Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water

FIRST AID MEASURES

Refer to **MSDS** for **Acryloc Roof Clean** before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on **1300 661 745** or visit **www.acryloc.com.au**

Ingestion

If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Drink at least two (2) glasses of water. Seek medical attention.

Eye

Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

Advice to Doctor

Treat symptomatically

MANUFACTURED BY:

Bizfine Pty Ltd

T/A Acryloc Building Products

174 Cavan Rd

DRY CREEK

South Australia 5094

P: +61 8 8368 0222

F: +61 8 8349 4260

E: sales@acryloc.com.au

W: www.acryloc.com.au