

ACRYLOC® CEILING WHITE

PRODUCT TYPE

Exported Paints – EXP201

PACKAGING

5L, 20L Heavy Duty Plastic Pail

NOMINAL WEIGHT

7.5kg, 30kg respectively

DESCRIPTION

Acryloc Ceiling *White* is a high quality, low odour, interior/exterior product, suitable for all interior ceilings and for exterior eave linings and portico & veranda ceilings, including areas normally susceptible to mould/mildew.

Acryloc Ceiling *White* is formulated to give high hiding power in a low spatter formulation.

FEATURES & BENEFITS

- Excellent water resistance
- Excellent vapour permeability
- Low Odour
- High hiding power
- Easy to apply, low spatter formula
- Water based, Easy & safe clean up

SUBSTRATE PREPARATION

- Areas not to be coated should be masked and protected

New Unpainted Surfaces

Fill nail holes, cracks and imperfections with an appropriate patching material and sand smooth.

Remove dust and make sure that the surface is clean, sound and free from contaminants such as oil, mould release, silicone, grease and efflorescence.

Apply one coat of Acryloc Interior Primer, EXP101.

Previously painted surfaces

Wash down with sugar soap and rinse with clean water.

Check for soundness of the original coating, remove any loose or flaking paint, fill holes and cracks and sand to an even finish.

Gloss or Semi-Gloss finishes must be completely dulled by sanding.

Apply one coat of Acryloc Interior Primer, EXP101.

Important Notes

- Application should be carried out on a day with temperatures above 10°C and below 32°C.

APPLICATION

- Mix thoroughly and check that the colour (if tinted) is correct before commencing work. Thinning is not normally required but up to 100mL of clean water per litre of paint can be added to the first coat when spraying or in warm conditions.
- Apply 2 full even coats of Acryloc Ceiling *White* by brush, spray or roller.
- For Roller application, a medium nap (12mm) roller is recommended. High quality synthetic rollers give best performance. Use a 13 or 15 thou spray tip with Airless spray.

Clean-Up

- Clean up with water

OTHER CONSIDERATIONS**Shelf-Life – Unopened Containers**

Maximum two (2) years from date of manufacture when stored correctly

Transport & Storage

Pails should not be stacked more than three (3) high during transportation and must be transported upright

Store in a cool place, upright, out of direct sunlight and above 4°C

For further information refer to **MSDS** for Acryloc Ceiling *White*

TECHNICAL DATA

APPEARANCE	Viscous white liquid		
ODOUR	Low		
APPLICATION METHODS	Roller, brush, spray		
SPECIFIC GRAVITY (NOMINAL)	1.4 -1.6		
THEORETICAL COVERAGE	6.5 - 8m ² /L per coat		
DRY TIME (25°C & 50% RH) (APPROX)	Tack Free	Recoat/ Overcoat	Fully Dried
	1 hour	2 hours	48 hours
NO. OF COATS	2		
GLOSS LEVEL	Flat		

SAFETY & HANDLING

Refer to **MSDS** for **Acryloc Ceiling White** before use. For further information on Material Safety Data Sheets, call the Acryloc **Tech – Info line** on **1300 661 745** or visit **www.acryloc.com.au**

When working with **Acryloc Ceiling White** observe the usual precautions for handling acrylic water based products including:

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact
- Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water

Full pails are **HEAVY**. Wear protective footwear and seek assistance if necessary.

FIRST AID MEASURES

Refer to **MSDS** for **Acryloc Ceiling White** before use. For further information on Material Safety Data Sheets, call the Acryloc **Tech – Info line** on **1300 661 745** or visit **www.acryloc.com.au**

If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Drink at least two (2) glasses of water. Seek medical attention.

Eye

Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

Advice to Doctor

Treat symptomatically

MANUFACTURED BY:

Bizfine Pty Ltd

T/A Acryloc Building Products

174 Cavan Rd

DRY CREEK

South Australia 5094

P: +61 8 8368 0222

F: +61 8 8349 4260

E: sales@acryloc.com.au

W: www.acryloc.com.au